



PREMO

PREMIUM PARTITION

TECHNICAL DATA SHEET

Integral modular partition system
Demountable partition
Reinstallation possibility
Hidden and visible profiling components
Normative applied reference UNE 41955



Thickness	82 mm.
Acoustic	42 dB.
Module	Width standard 1200 mm, variable Height: up to 6000 mm.
Interior supports	Sendzimir galvanized steel 0,7 mm. Mechanical Properties EN 10346 Height regulation by machining steel square
Exterior profiles	Extruded aluminium in accordance EN-755 y EN-573-3 Anodised or lacquered aluminium Qualicoat requirements
Panels	13 mm. woodchip hardboard panel decorative coated. Coating options: melamine, high pressure laminate, wood, textile, vinile... Panels hold by zetas and panel clips causing demountability possibility
Glass panes	Thickness of between 3+3 and 6+6 mm. Panes junction by profile or fine transparent polycarbonate H
Doors	Thickness: 40mm. and 82 mm. flush door Standard height 2047 mm. Possibility floor to ceiling Simple, double, sliding doors Blind, pane o r mixed. Frame panel or rail. One or two panes framed
Interior	50 mm. thick rock wool. AW 0.70. UNE EN 13162 for thermal and acoustic insulation
Panel joints	3 mm. or 10 mm groove with aluminium profile Cover plate of aluminum